

The ILLUMRA 5A On/Off Controller is a line-voltage controller that allows lights to be controlled by ILLUMRA self-powered switches, occupancy sensors, light sensors, and gateways to implement power saving strategies.

Use as part of a wireless control system to reduce energy consumption or to implement compliance with the latest energy regulations.

Features:


- On/Off control for individual LED and fluorescent luminaires and 5A loads
- Reduce energy consumption
- Extend equipment life

Typical Applications:

- Conference rooms
- Classrooms
- Offices
- Remodels & Retrofits
- Daylight harvesting

Compatible Devices:

- Wireless Light Switches
- Key Card Switch
- Control Transmitter
- Wireless Occupancy Sensor
- Window/Door Sensor
- Light Sensor
- Gateway



115 S State St, Suite B Lindon, UT 84042

T: (801) 349-1200 F: (801) 614-7100 Sales@ILLUMRA.com


5A On/Off Controller

E9X-RUV-3HOTP

- Fast installation. Install one controller per light, avoiding the need to run wires between fixtures.
- Interoperable. Communicates wirelessly with other devices using the EnOcean wireless standard. Easy integration with your building management system.



WIRING DIAGRAM



SPECIFICATIONS

100-277 VAC 50/60 Hz
5A all loads, Induction, Fluorescent, LED, Other 70A Max Inrush Current 1/4 HP
EnOcean® Protocol 902 MHz
50-150 feet (typical)
2.61 x 1.73 x 1.09 inches (66 x 44 x 28mm)
+32 to +122°F (0 to +50°C)
-4 to +176°F (-20 to +80°C)
UL 60730 (safety) UL 2043 (plenum) CSA c22.2#14-05 (safety) CE - IEC 60730 FCC ID: SZV-STM300U IC ID: 5713A-STM300U