

Project Name

Location

Prepared By



NUVO 65-755

LED WALL PACK CCT & WATT ADJ

Notes

[www] 04-25-2022 02:43:09

General

Status	Active
Fixture Type	Wall Pack
Finish	Bronze
Wattage	29W/40W/60W
Lumen Output	4060L-8640L
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
IP Rating	IP65
Indoor or Outdoor Fixture	Indoor and Outdoor

Specifications

Technology	LED
CRI	80+
Voltage	120V-277V
Beam Angle	110
Rated Hours	50000
Operating Temperature	-40C (-40F) to a maximum of +50C (+122F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Photocell	Yes - bypassable
Lens Material	Polycarbonate (PC) and Glass
Surge Protection	Built-in surge protection - 4KV
Weight (lb.)	9.5
Material	Die Cast Aluminum

Dimensions

Height (in.)	9.35
Width (in.)	14.36
Extension (in.)	7.39

Compliance

Safety Listing	cULus - Listed; cULus - Certified
Location Rating	Wet
Energy Star	No
DLC Approved	Yes
DLC ID	PLH1XW3LK38T
ADA Compliant	No
CA T20 / T24 Rationale	California T24 2016 & 2019 JA8 Compliant
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Compliant
California Prop 65	Lead
FCC Compliant	Yes

Additional Information

Warranty	5 Year Limited
----------	----------------

Project Name

Location

Prepared By



NUVO 65-756

LED WALL PACK CCT & WATT ADJ

Notes

[www] 04-25-2022 02:43:09

General

Status	Active
Fixture Type	Wall Pack
Finish	Bronze
Wattage	80W/100W/120W
Lumen Output	11200L-17280L
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
IP Rating	IP65
Indoor or Outdoor Fixture	Indoor and Outdoor

Specifications

Technology	LED
CRI	80+
Voltage	120V-277V
Beam Angle	110
Rated Hours	50000
Operating Temperature	-40C (-40F) to a maximum of +50C (+122F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Photocell	Yes - bypassable
Lens Material	Polycarbonate (PC) and Glass
Surge Protection	Built-in surge protection - 4KV
Weight (lb.)	9.5
Material	Die Cast Aluminum

Dimensions

Height (in.)	9.35
Width (in.)	14.36
Extension (in.)	7.39

Compliance

Safety Listing	cULus - Listed; cULus - Certified
Location Rating	Wet
Energy Star	No
DLC Approved	Yes
DLC ID	PLQBZSSZVMBW
ADA Compliant	No
CA T20 / T24 Rationale	California T24 2016 & 2019 JA8 Compliant
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Compliant
California Prop 65	Lead
FCC Compliant	Yes

Additional Information

Warranty	5 Year Limited
----------	----------------

Project Name

Location

Prepared By



NUVO 65-757

LED WALL PACK CCT & WATT ADJ

Notes

[www] 04-25-2022 02:43:09

General

Status	Active
Fixture Type	Wall Pack
Finish	Bronze
Wattage	29W/40W/60W
Lumen Output	4118L-8770L
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
IP Rating	IP65
Indoor or Outdoor Fixture	Indoor and Outdoor

Specifications

Technology	LED
CRI	80+
Voltage	120V-347V
Beam Angle	110
Rated Hours	50000
Operating Temperature	-40C (-40F) to a maximum of +50C (+122F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Photocell	Yes - bypassable
Lens Material	Polycarbonate (PC) and Glass
Surge Protection	Built-in surge protection - 4KV
Weight (lb.)	9.5
Material	Die Cast Aluminum

Dimensions

Height (in.)	9.35
Width (in.)	14.36
Extension (in.)	7.39

Compliance

Safety Listing	cULus - Listed; cULus - Certified
Location Rating	Wet
Energy Star	No
DLC Approved	Yes
DLC ID	PL1MK0MX6TQL
ADA Compliant	No
B.U.G. Rating	B1-U4-G5
CA T20 / T24 Rationale	California T24 2016 & 2019 JA8 Compliant
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Compliant
California Prop 65	Lead
FCC Compliant	Yes

Additional Information

Warranty	5 Year Limited
----------	----------------



Project Name

Location

Prepared By



NUVO 65-758

LED WALL PACK CCT & WATT ADJ

Notes

[www] 04-25-2022 02:43:09

General

Status	Active
Fixture Type	Wall Pack
Finish	Bronze
Wattage	80W/100W/120W
Lumen Output	11360L-17400L
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
IP Rating	IP65
Indoor or Outdoor Fixture	Indoor and Outdoor

Specifications

Technology	LED
CRI	80+
Voltage	120V-347V
Beam Angle	110
Rated Hours	50000
Operating Temperature	-40C (-40F) to a maximum of +50C (+122F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Photocell	Yes - bypassable
Lens Material	Polycarbonate (PC) and Glass
Surge Protection	Built-in surge protection - 4KV
Weight (lb.)	9.5
Material	Die Cast Aluminum

Dimensions

Height (in.)	9.35
Width (in.)	14.36
Extension (in.)	7.39

Compliance

Safety Listing	cULus - Listed; cULus - Certified
Location Rating	Wet
Energy Star	No
DLC Approved	Yes
DLC ID	PLQPRK37PQUE
ADA Compliant	No
B.U.G. Rating	B2-U4-G5
CA T20 / T24 Rationale	California T24 2016 & 2019 JA8 Compliant
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Compliant
California Prop 65	Lead
FCC Compliant	Yes

Additional Information

Warranty	5 Year Limited
----------	----------------

For More Information Visit:



