

Project Name

Location

Prepared By



NUVO 65-760

LED CUTOFF WALL PACK CCT&WATT

Notes

General	
Status	Active
Fixture Type	Wall Pack
Finish	Bronze
Wattage	29W/40W/60W
Lumen Output	3915L-8400L
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
IP Rating	IP65
Indoor or Outdoor Fixture	Indoor and Outdoor
Specifications	
Technology	LED
CRI	80+
Voltage	120V-277V
Beam Angle	110
Rated Hours	50000
Operating Temperature	-40C (-40F) to a maximum of +50 (+122F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Photocell	Yes - bypassable
Lens Material	Polycarbonate (PC) and Glass
Surge Protection	Built-in surge protection - 10KV
Weight (lb.)	10.5
Material	Die Cast Aluminum
Dimensions	
Height (in.)	9.83
Width (in.)	14.26
Extension (in.)	9.33

Dimensions	
Height (in.)	9.83
Width (in.)	14.26
Extension (in.)	9.33

Compliance	
Safety Listing	cULus - Listed; cULus - Certified
Location Rating	Wet
Energy Star	No
DLC Approved	Yes
DLC ID	PLGG00BXA47N
ADA Compliant	No
B.U.G. Rating	B2-U3-G3
CA T20 / T24 Rationale	California T24 2016 & 2019 JA8 Compliant
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Compliant
California Prop 65	Lead
FCC Compliant	Yes

0000

5 Year Limited Warranty

Additional Information

SATCO NUVO

Project Name

Location

Prepared By



NUVO 65-761

LED CUTOFF WALL PACK CCT&WATT

Notes

[www] 04-25-2022 02:43:

General		
Status	Active	
Fixture Type	Wall Pack	
Finish	Bronze	
Wattage	80W/100W/120W	
Lumen Output	10800L-15600L	
CCT (Kelvin)	3000K/4000K/5000K	
Temperature	Warm to Cool White	
IP Rating	IP65	
Indoor or Outdoor Fixture	Indoor and Outdoor	
Specifications		
Technology	LED	
CRI	80+	
Voltage	120V-277V	
Beam Angle	110	

Technology	LED
CRI	80+
Voltage	120V-277V
Beam Angle	110
Rated Hours	50000
Operating Temperature	-40C (-40F) to a maximum of +50C (+122F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Photocell	Yes - bypassable
Lens Material	Polycarbonate (PC) and Glass
Surge Protection	Built-in surge protection - 10KV
Weight (lb.)	10.5
Material	Die Cast Aluminum

Compliance	
Safety Listing	cULus - Listed; cULus - Certified
Location Rating	Wet
Energy Star	No
DLC Approved	Yes
DLC ID	PLV84B3C1BRR
ADA Compliant	No
CA T20 / T24 Rationale	California T24 2016 & 2019 JA8 Compliant
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Compliant
California Prop 65	Lead
FCC Compliant	Yes

9.83

14.26

9.33

Additional Information

Warranty

Height (in.)

Width (in.)

Extension (in.)

5 Year Limited









