

# L47

## EXTERIOR | INTERIOR

Vertical Steplight | For walls, stairs, and walkways.

- Wet, Damp, and Dry Location



Engraving Option

### Ordering Information

Clear Form

Date :	<input type="text"/>	Quantity :	<input type="text"/>
Project :	<input type="text"/>	Note :	<input type="text"/>
Type :	<input type="text"/>		<input type="text"/>

### Specifications

Luminaire | Example Code: L47-6-W30H-MK1-E-S6

Product	Version	CCT & CRI	Mounting Kit <sup>1</sup> (optional)	Engraving <sup>2</sup> (optional)	Finish <sup>3</sup>
L47					
	3 3W 6 6W	W22S 2200K 80+ W27H 2700K 90+ W30H 3000K 90+ W35H 3500K 90+ W41H 4100K 90+	MK1 vertical surface	E engraving	<b>Aluminum Finishes:</b> MA matte clear anodized BK black powder coated WH white powder coated BZ bronze powder coated  <b>Stainless Steel Finish:</b> S6 stainless steel 316

### System Components (Ordered Separately)

Remote Driver :

\* Consult Website or Factory.

### Important Notes

#### Specifications

- Mounting kit is ordered separately (consult factory). Back box must also be purchased with MK1 kit.
- Engraving is only available for MA and S6 finishes.
- Refer to Appendix or website for complete look of luminaire with different finish options.

# L47

## EXTERIOR | INTERIOR

Vertical Steplight | For walls, stairs, and walkways.

• Wet, Damp, and Dry location



Engraving Option

### Performance

Wattage	Forward Current	Power Consumption Budget per fixture (including driver)	LED output (Source)	Fixture Output (Delivered)
3W	350mA	4W	330 lm	43.9 lm
6W	700mA	8W	660 lm	87.8 lm

### Application

Environment	Dry / Damp / Wet Location approved. IP 66.
Mounting	Mounts to vertical oriented single gang box. <b>Box opening: Width   2-3/8" (60.33mm) X Height   2" (50.8mm)</b>  <b>MK1 mounting kit (optional):</b> Recommended for easy installation on vertical surfaces (e.g. stair risers, walls). See "Mounting Options & Dimensions, "

### Electrical

Power Supplies	Non-dimmable integral driver included (100-240V AC input). Compatible with remote driver for wet locations (not included).
Control	<b>On/off control</b> <b>Dimming(consult factory):</b> ELV or 0-10V dimming with appropriate drivers <b>Other options (consult factory):</b> TRIAC/MLV, DMX, DALI, Casambi, Power over Ethernet

### Luminaire Construction

LED Light Source	<b>W22S</b> = CCT: 2200K, CRI (Ra): 80+, Colour Consistency: 3SDCM <b>W27H</b> = CCT: 2700K, CRI (Ra): 90+, Colour Consistency: 2SDCM <b>W30H</b> = CCT: 3000K, CRI (Ra): 90+, Colour Consistency: 2SDCM <b>W35H</b> = CCT: 3500K, CRI (Ra): 90+, Colour Consistency: 2SDCM <b>W41H</b> = CCT: 4100K, CRI (Ra): 90+, Colour Consistency: 3SDCM
Standard Compliance	✓ADA-compliant    ✓WELL standard – Feature 58: Color Quality
Weight	1.5 lbs (0.68 kg). Typical Aluminum Fixture.
Material	<b>Fixture:</b> machined marine-grade aluminum or machined stainless steel (316) with tempered glass
Supplied with	<b>Driver:</b> Non-dimmable integral driver included.
Warranty & LED Life	5 years limited warranty Estimated useful life of LED is 50,000 hours.


### Ordered Separately

System Components	<b>Power supplies:</b> alternate remote driver for dimming options Please consult factory for available driver options. <b>Mounting kit:</b> MK1 & Back box <b>Custom back boxes:</b> see Pg.3- Mounting Options & Dimensions.
-------------------	---


## Mounting Options & Dimensions

### LED Insert Dimensions

Fixture




Side View



3D View



Beam




### Custom Rectangular Back Box for Wall Installation


1. For wall installation, custom rectangular electrical boxes are available as alternative options.

#### Single Gang Back Box | Order Code: EBX-SGB1

Top View




Side View




#### Scepter FD Back box | Order Code: EBX-SFD

Top View



Side View



## MK1 | For walls and stairs

Mounting Kit Exploding Views \* *Back box not included*



MK1-SGB1

MK1-SGB1 shown with EBX-SGB1


MK1-SGB1 shown with EBX-SGB1 and Plywood Form

Wall-mount Plywood Form Installation (shown with L47)




## 3W, 3000K, 90+ CRI

### Polar Candela Distribution



### Isofootcandle Plot




### Illuminance at a Distance

Distance		Center Beam fc	Beam Width			
1.5ft	0.45m	7.15fc	3.5ft	1.06m	0.4ft	0.12m
3.0ft	0.91m	1.79fc	7.1ft	2.16m	0.9ft	0.27m
4.5ft	1.37m	0.79fc	10.6ft	3.23m	1.3ft	0.39m
6.0ft	1.82m	0.45fc	14.1ft	4.29m	1.7ft	0.51m


Delivered Lumens: 54.7lm  
■ Vertical Beam Spread: 99.3°  
■ Horizontal Beam Spread: 16.5°

## 6W, 3000K, 90+ CRI

### Polar Candela Distribution



### Isofootcandle Plot



### Illuminance at a Distance

Distance		Center Beam fc	Beam Width			
1.5ft	0.45m	12.9fc	3.6ft	1.09m	0.4ft	0.12m
3.0ft	0.91m	3.22fc	7.1ft	2.16m	0.4ft	0.27m
4.5ft	1.37m	1.43fc	10.7ft	3.26m	1.3ft	0.39m
6.0ft	1.82m	0.80fc	14.2ft	4.32m	1.8ft	0.54m

Delivered Lumens: 91.6lm  
■ Vertical Beam Spread: 99.7°  
■ Horizontal Beam Spread: 16.9°

## Appendix

### Aluminum Finishes



MA matte clear anodized



BK black powder coated



BZ bronze powder coated



WH white powder coated

### Stainless Steel Finish



S6 stainless steel 316