

PD-56729

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Zelda

PD-56729

PRODUCT DESCRIPTION

Inspired by ocean ripples, the Zelda Pendant by Modern Forms brings a fluid, yet soothing ambiance to your interior decor. Its ringed body, made of Die Cast Aluminum, isartisan-sculpted to resemble gently flowing water which appears to run around the fixture in constant motion. An Opal glass diffuser sits flush at the base of the ring, providing a soft, low-profilelight courtesy of an integrated LED source.

FEATURES

- 277V option available for special order.
- ACLED driverless technology
- Downward illumination
- · Can be mounted on a sloped ceiling

SPECIFICATIONS

Rated Life 54000 Hours

Standards ETL, cETL, Damp Location Listed

Input 120 VAC,50/60Hz

 Dimming
 ELV

 Color Temp
 3000K

 CRI
 90

Construction Die-cast aluminum

REPLACEMENT PARTS

RPL-GLA-56729-01 - Glass


Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-56729 29"	3000K	PN Polished Nickel	48.6W	2388	1236

Example: PD-56729-PN

•For 277V special order, add an "F" before the finish: PD-56729F-PN

For custom requests please contact customs@modernforms.com





PD-56748

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Zelda

PD-56748

PRODUCT DESCRIPTION

Inspired by ocean ripples, the Zelda Pendant by Modern Forms brings a fluid, yet soothing ambiance to your interior decor. Its ringed body, made of Die Cast Aluminum, isartisan-sculpted to resemble gently flowing water which appears to run around the fixture in constant motion. An Opal glass diffuser sits flush at the base of the ring, providing a soft, low-profilelight courtesy of an integrated LED source.

FEATURES

- 277V option available for special order.
- Transformer concealed within the canopy
- Downward illumination
- · Can be mounted on a sloped ceiling
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 48" format exceeds 50 lbs. and must be installed using a U.L. listed outlet box approved for up to 100 lbs. or supported independently of the outlet box

SPECIFICATIONS

Rated Life 54000 Hours

Standards ETL, cETL, Damp Location Listed

Input 120 VAC,50/60Hz

Dimming ELV
Color Temp 3000K
CRI 90

Construction Die-cast aluminum

REPLACEMENT PARTS

RPL-GLA-56748-01 - Glass

Model & Size	Color Temp	Finish		LED Watts	LED Lumens	Delivered Lumens
PD-56748 48"	3000K	PN	Polished Nickel	94W	3582	3060

Example: PD-56748-PN

•For 277V special order, add an "F" before the finish: PD-56748F-PN

For custom requests please contact customs@modernforms.com