

CATENARY CABLE

1/8" Cable & Locks

Multi-purpose cable with cable locks for quick, reliable support up to 330 pounds of load. Order catenary wire in kits, which include the cable locks for each end or in bulk (500ft roll, cable locks sold separately).

- Provides support for spans of Commercial Grade Light String, Festoon Light String, and other linear lighting products
- 1/8" diameter outdoor rated, galvanized cable and clips resist corrosion
- Cable fasteners can be attached without the use of tools and can be adjusted quickly and easily
- Tensioning Tool allows you to tension wire up to 880lbs with minimal effort due to the 6:1 gear drive mechanism
- The integral torque gauge controls the load applied to the wire, giving consistent tension every time and optimizing the life of the wire



CATENARY CABLE QUICK SPECS

SERIES	LS-CABLE
MAX WEIGHT RATING	Horizontal: 70lbs, with 5:1 safety factory 350lbs Vertical: 200lbs
RATING	Suitable for indoor/outdoor use
CABLE DIMENSIONS	1/8" (3mm) Dia. Galvanized Steel Cable

CATENARY CABLE ORDERING INFORMATION

ITEM NUMBER	MAX RUN
LS-CABLE-60	60ft Kit / Includes 2 Heavy Duty Cable Locks (330lbs rating)
LS-CABLE-110	110ft Kit / Includes 2 Heavy Duty Cable Locks (330lbs rating)
LS-CABLE-500	500ft Catenary Cable Bulk Reel
LS-LOCK-4	4-Pack Heavy Duty Cable Locks
LS-TT	Tensioning Tool


Includes: Catenary Cable Kits include: (2) Heavy Duty Cable Locks / (1) Cable Release Key

PROJECT:

TYPE:

LOCATION:

CATALOG NUMBER:





AMERICAN LIGHTING WARRANTY

LIMITED WARRANTY FOR LED PRODUCTS: 1 YEAR

LIMITED PRODUCT WARRANTY

Our products are warranted to be free from defects in material and workmanship for the warranty period listed. Warranty periods begin from the date of shipment from American Lighting Inc's warehouse to the original purchaser. Products that prove to be defective during their specific warranty period will be either repaired or replaced, at the sole discretion of American Lighting Inc. Claims for defective products must be submitted in writing to American Lighting Inc's RGA Department within the warranty period. Upon approval of such return, American Lighting Inc reserves the right to inspect the product for misuse or abuse. Claims for indirect or consequential damages or for product that, in American Lighting Inc's opinion, has been misused will be denied. This is a warranty of product reliability only and not a warranty of merchantability or fitness for a particular purpose. American Lighting Inc shall have no liability whatsoever in any event for payment of incidental or consequential damages, including, without limitations, installation costs and/or damages for personal injury and/or property. These products may represent a possible shock or fire hazard if improperly installed or altered in any way. This warranty does not apply to any product that has not been properly installed in accordance with current local codes and/or the National Electrical Code. Products that require a transformer, driver, or power supply must be used in conjunction with American Lighting Inc's recommended power supply to ensure safety and retain product warranty.

PRODUCT SPECIFICATIONS

For the latest product information, updates, instructions and details concerning specifications, colors, finishes, performance, installation and design, visit www.americanlighting.com.

Color may vary from the color printed herein due to limitations in photographic and printing processes. American Lighting Inc. reserves the right to change product specifications without notice. Other product specifications such as color temperature, wavelength characteristics and lumen output are subject to production limitations and may vary.

LED technology is changing rapidly, and not all color temperatures and performance levels can be duplicated at a later time. Best practices include purchasing 10-15% more for a particular project on the same initial order where white LED color temperatures must be maintained over project and product life. Eventual product replacement should be considered at layout and design stages. Best practices also include testing connections and product performance prior to mounting and/or installing.

AVERAGE LIFE

Average incandescent lamp life, rated life and average life are terms used to describe the number of hours at which half of the lamps have failed. For LEDs, the hours of rated life specify the point where 70% of original lumen output is reached. Below this point, the effective life is over, however, the LED may still emit light. Individual results may vary with actual environmental conditions including, but not limited to, proper installation, ambient temperature and/or input voltage fluctuations.